

RESISTORS		
10R	2	R101, R102
560R	2	R212, R213
1K	12	R202, R204, R207, R215, R217, R218, R223, R225, R310* , R506, R508, R511 *3300ppm/C Tempco if temperature stability required
2K2	1	R312
10K	7	R201, R203, R205, R221, R222, R224, R512
12K	4	R209, R211, R219, R507
22K	5	R404, R406, R502, R505, R509
33K	2	R206, R216
51K	2	R303, R309
100K	15	R301, R302, R306, R307, R311, R401, R402, R403, R407, R409, R501, R503, R504, R510, R513
200K	2	R405, R408
300K	1	R304

CAPACITORS		
220pF	4	C201, C202, C303, C304
100nF	10	C203, C204, C205, C206, C207, C208, C301, C302, C501, C502
100uF	2	C101, C102

POTENTIOMETERS		
1K 25-turn	3	RV201, RV202, RV501
10K 25-turn	1	RV306
100K 25-turn	1	RV302
100K linear	5	RV301, RV304, RV305, RV401, RV402

SEMICONDUCTORS		
1N4148	5	D201, D202, D203, D204, D501
BC560	2	Q301, Q302 Match if temperature stability required

INTEGRATED CIRCUITS		
LM13700	2	U202, U203
TL072	1	U501
TL074	2	U201, U301

CONNECTORS		
Banana Jacks	10	
IDC 10-pin Shrouded Header	1	P101 (Option 1)
MTA-156 4-pin Header	1	P101 (Option 2)
16-pin IC socket	2	
14-pin IC socket	2	
8-pin IC socket	1	
10-pin 2.54mm pin header	2	Use standard breakaway strip
10-pin 2.54mm female pin header	2	

HARDWARE		
M3 x 20mm Screw	4	
M3 Washer	16	
10mm Threaded Metal Hex Spacer	4	
M3 Nut	4	